

01/06/00  
jc682 U.S. PTO

01-10-00

A

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)  
Approved for use through 09/30/2000. OMB 0651-0032  
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 518900-0010  
First Inventor or Application Identifier Steven C. Sims  
Title ARCHERY BOWS  
Express Mail Label No. EL006818583US

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1. ☐ \* Fee Transmittal Form (e.g., PTO/SB/17)  
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 35]  
(preferred arrangement set forth below)
- Descriptive title of the Invention
  - Cross References to Related Applications
  - Statement Regarding Fed sponsored R & D
  - Reference to Microfiche Appendix
  - Background of the Invention
  - Brief Summary of the Invention
  - Brief Description of the Drawings (if filed)
  - Detailed Description
  - Claim(s)
  - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 6]
4. Oath or Declaration [Total Pages 41]
- a. ☐ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))  
(for continuation/divisional with Box 16 completed)
- i. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement of Power of Attorney (when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 [Copies of IDS Citations]
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
13. ☐ \* Small Entity Statement(s) filed in prior application, Status still proper and desired (PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☐ Other:

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: \_\_\_\_\_

Prior application information: Examiner \_\_\_\_\_ Group / Art Unit: \_\_\_\_\_

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.


## 17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label or ☒ Correspondence address below  
(Insert Customer No. or Attach bar code label here)

Name	Richard D. Multer				
Address	Miller Nash LLP 4400 Two Union Square, 601 Union Street				
City	Seattle	State	WA	Zip Code	98101-2342
Country	USA	Telephone	(206) 622-8484	Fax	(206) 622-7485

Name (Print/Type)	Richard D. Multer	Registration No. (Attorney/Agent)	20,661
Signature	<i>Richard D. Multer</i>	Date	January 6, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.



Attorney's Docket No.: 518900-0010

In re application of:

Serial No.:

Filed: 06 January 2000

Applicants: Sims

Title: ARCHERY BOWS

Box New Application  
Assistant Commissioner of Patents  
Washington, D.C. 20231

### CERTIFICATE OF MAILING

The following documents are today being deposited with the United States Postal Service "Express Mail (Express Mail Label No. EL006818583US) Post Office to Addressee" service under 37 C.F.R. 1.10 in an envelope addressed to Box New Application, Assistant Commissioner for Patents, Washington, D.C. 20231:

- (1) *Utility Patent Application* Cover Sheet;
- (2) 35 pages of Specification;
- (3) 6 sheets of Drawings;
- (4) a certificate of mailing; and
- (5) an itemized return receipt postcard.

Signed at Seattle, Washington this 6<sup>th</sup> day of January 2000.

Respectfully submitted,  
STEVEN C. SIMS

By *Richard D. Multer*  
Richard D. Multer  
Reg. No. 20,661  
Miller Nash LLP  
4400 Two Union Square  
601 Union Street  
Seattle, Washington 98101

Tel.: 206.622.8484  
Fax: 206.622.7485

## ARCHERY BOWS

### TECHNICAL FIELD OF THE INVENTION

The present invention relates to archery bows, and more particularly, to novel, improved bows with accessories which improve accuracy by modifying the decay pattern of the vibrations set up in the bow when an arrow is released.

### BACKGROUND OF THE INVENTION

The release of an arrow from even a modern bow sets up significant vibrations in the limbs of the bow, and these are in large part transmitted to the riser of the bow and from there to the archer's hand. The result is a significant adverse effect on accuracy.

A variety of stabilizers have been employed in an effort to reduce the adverse effect of this vibration on the accuracy of the bow. At best, such devices have proved to be of limited value.

## SUMMARY OF THE INVENTION

There have now been invented and disclosed herein certain new and novel vibration decay pattern modifiers which significantly reduce the adverse effect on accuracy of the vibrations generated when an arrow is released. Different ones of these decay pattern modifiers are fixed to the limbs of the bow and/or to the end of the hydraulic stabilizer typically attached to the riser of a compound bow.

Decay pattern modifiers in accord with the principles of the present invention are fabricated from a soft visco-elastic polymer and have a mushroom-like configuration provided by a head and an integral stem. The head and stem of the decay pattern modifiers are so configured and dimensioned that: (1) the modifier can vibrate or oscillate toward and away from the longitudinal axis of the modifiers at any and all locations around the 360° circumference of the modifier, and (2) peripheral portions of the decay pattern modifier head can oscillate in directions generally parallel to the longitudinal modifier axis at any (and all) locations around the circumference of the decay pattern modifiers. Motions are also set up in the material of the damper. The combined result of these motions is a wiggle and jiggle which significantly alters

the pattern of vibrations set up in the bow when an arrow is released, effectively minimizing the effect on accuracy of those vibrations

Yet another, particularly important advantage of the present invention is that there is only a small, two foot per second (typical) loss in arrow velocity appurtenant to the use of decay pattern modifiers embodying its principles.

Another important attribute of the novel decay pattern modifiers disclosed herein is that they are light and small enough that they do not interfere with the normal drawing of the bow string and subsequent release of an arrow.

Other important objects, features, and advantages of the invention will be apparent to the reader from the foregoing and the appended claims and as the ensuing detailed description and discussion of the invention proceeds in conjunction with the accompanying drawing.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a pictorial view of a compound bow equipped with decay pattern modifiers constructed in accord with the principles of the present invention; components of the

bow which are not relevant to an understanding of the present invention do not appear in FIG. 1;

these include the bow sight and the often present, built-in quiver;

FIG. 2 is an exploded view, to an enlarged scale, of one of two identical decay pattern modifiers with which the bow of FIG. 1 is equipped;

FIG. 3 is a fragmentary section through one limb of the FIG. 1 bow and the decay pattern modifier attached to that limb;

FIG. 4 shows an alternate location on the bow link for the decay pattern modifier;

FIG. 5 shows a second decay pattern modifier with an alternate mechanism for attaching the decay pattern modifier to the limb of a bow;

FIG. 6 is a section through the FIG. 5 decay pattern modifier;

FIG. 7 is a fragmentary view of a second compound bow which is of the split limb type and which is equipped with decay pattern modifiers in accord with the principles of the present invention;

FIG. 8 is an enlarged and isometric view of a decay pattern modifier as shown in FIG. 7;

FIG. 9 is a view similar to FIG. 7 but showing an alternate form of decay pattern modifier designed for use with split limb bows;

FIG. 10 is an exploded view of the decay pattern modifier depicted in FIG. 9;

FIG. 11 is a longitudinal section through the decay pattern modifier of FIG. 10;

FIG. 12 is a fragmentary view of a bow equipped with: (1) a conventional, hydraulic type bow stabilizer, and (2) a stabilizer-associated accessory for modifying vibration decay patterns in accord with the principles of the present invention;

FIG. 13 is a perspective view of the decay pattern modifier illustrated in FIG. 12;

FIG. 14 is a side view of the FIG. 12 decay pattern modifier;

FIG. 15 is an imploded view of a second type of limb saver which embodies the principles of the present invention and is designed to be attached to a bow stabilizer;

FIG. 16 is a section through the FIG. 15 decay pattern modifier and the outboard end of a bow stabilizer to which the accessory is attached;

FIGS. 17 and 18 are graphs showing the significant effect beneficial alteration of bow vibration pattern that can be realized by employing decay pattern modifiers as illustrated in FIGS. 1-3;

FIG. 19 is a fragmentary view, similar to FIG. 4, of a bow limb and yet another form of decay pattern modifier embodying the principles of the present invention;

FIG. 20 is a perspective view of the FIG. 19 limb saver; and

FIG. 21 is a section through the FIG. 20 decay pattern modifier.

### DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, FIG. 1 depicts a compound bow 20 equipped with decay pattern modifier 22 and 24 in accord with the principles of the present invention. Bow 20 has flexible limbs 26 and 28 mounted to the opposite ends of a riser 30 and a bow string 32. The bow string is strung around cams 34 and 36 at the ends of limbs 26 and 28. The ends of the bow string are anchored to the shafts 38 and 40 which support cams 34 and 36 from the limbs 26 and 28 of bow 20.

The two decay pattern modifiers 22 and 24 are duplicates; accordingly, only decay pattern modifier 24, shown in more detail in FIGS. 2 and 3, will be considered in detail herein.

Decay pattern modifier 24 has a mushroom-like configuration and a T-like cross-section defined by a cylindrical head 42 and an integral, also cylindrical stem 44. Decay



pattern modifier 20 is fabricated from a soft, visco-elastic material; preferably, a visco-elastic material with a Shore A hardness in the range of three to 20. The ratio between the diameter of decay pattern modifier head 42 and the length of stem 44 is preferably kept between 1:1 and 5:1 for optimal effectiveness.

One suitable visco-elastic material is NAVCOM. NAVCOM is a soft, amorphous, rubber-like material which contains a mixture of chloroprene and butyl polymers and has the following physical properties (representative).

<u>Shore A hardness: 17-90</u>					
Environment	Shore A	Ultimate Elongation (Percent)	Tensile Strength (PSI)	Compression Set (Percent)	Specific Gravity
	7	1,075	373	6.01	1.014
	12	900	643	7.3	1.025
	20	835	1,069	6.9	1.063
	30	1,056	1,621	4.0	1.074
	40	326	1,453	N/A	1.185
	90	175	2,440	N/A	1.379
Oven aged	7	N/A	N/A	56.3	--
for	12	--	--	31.1	--
70 hrs at	20	--	--	30.8	--
212 ± 5° F.	40	--	--	22.4	--
	90	--	--	18.6	--

Resilience:	At room temperature – Medium
	At high temperature – Fairly high

Heat resistance	Good
Outdoor aging resistance:	Excellent
Low temp flexibility:	Good
Abrasion resistance:	Good
Flex life:	Good
<u>Solvent resistance:</u>	
Hydrocarbons -	Fair to good
Oxygenated -	Fair to good
Air permeability:	Low to moderate
Moisture resistance:	Fair
Useful operating temperature:	-40° to 250° F.

---

The nominal dimensions of the exemplary illustrated decay pattern modifier are:

Head 42:

Diameter:	1.44 in.
Width:	0.38 in.

Stem 44:

Diameter:	0.76 in.
Length:	0.25 in.

The stem 44 of decay pattern modifier 24 can vibrate toward and away from the longitudinal axis 46 of the device at any and all directions around the 360° circumference of modifier as indicated by ellipse 47 in FIG. 3. At the same time, the peripheral edge portion 52 of head 42 can oscillate back and forth at any and all locations around the 360° circumference of the head in directions generally paralleling longitudinal axis 46 as indicated by arrows 54 and 56. There may also be otherwise directed movement of the

modifier head and stem when and after an arrow is released as well as oscillations set up in the head and stem of the modifier. These oscillations and movements in total --herein referred to as "wiggle and jiggle"-- produce the beneficial shift in vibration decay patterns realized by employing a vibration decay pattern modifier as just disclosed as well as other such accessories embodying the principles of the present invention including those embodiments disclosed hereafter in this specification and illustrated in the drawings. These unique patterns of oscillatory movement have been found to be highly effective in modifying the patterns of vibration set up in a bow when an arrow is released in a positive manner.

The dramatic shift in the decay pattern of the vibrations set up in a bow when an arrow is released effected by devices as just described is dramatic as is shown in FIGS. 17 and 18. FIG. 17 shows that there is a significant reduction in the amplitude of the vibrations beginning at time zero (time of arrow release). The spatial analyses of FIG. 18 shows a similar, significant reduction in both the primary frequencies of the

vibrations set up in the bow when an arrow is released and in the harmonic frequencies of those vibrations.

As shown in FIGS. 2 and 3, the exposed end 58 of decay pattern modifier stem 44 is covered by a layer 60 of adhesive which is protected by a peel-off cover 62.

This makes the attachment of the decay pattern modifier to the associated limb of bow 20 a task of the utmost simplicity. All that is required is to remove cover 62 and then press the decay pattern modifier onto the limb of the bow at the selected location therealong.

In this regard, the decay pattern modifiers 22 and 24 are preferably located near the outer ends of the two limbs 26 and 28 of bow 20 (FIG. 1). The placing of the decay pattern modifiers at these locations has been found to be the most effective in modifying the vibrations set up in bow 20 when an arrow is released in a positive manner.

It is also preferred that the decay pattern modifiers 22 and 24 be mounted on the inner sides (63a and 63b) of the bow limbs 26 and 28; i.e., on the sides of those limbs facing bow string 32. This keeps the decay pattern modifiers from being snagged

as the bowman moves through brush or bushes, for example. The same, significant, worthwhile modification in the vibration decay pattern can nevertheless be obtained by mounting the decay pattern modifier on the outer sides 64a and 64b of the bow limbs. This arrangement is depicted in FIG. 4 which shows a decay pattern modifier 65 of the character described above mounted on the outer side 64a of bow limb 26.

FIGS. 4 and 6 of the drawings, to which reference is now made, depict an alternate arrangement for attaching a decay pattern modifier as described above to the limb of a bow; e.g., the limb 28 of bow 20. In this case, a threaded fastener 68 is embedded in the stem 70 of decay pattern modifier 72 with the threaded shank 74 of fastener 68 protruding from the stem. Shank 74 is screwed into an internally threaded fitting 76 mounted in the limb 28 of the bow as shown in FIG. 6. This securely attaches the decay pattern modifier to the limb of the bow.

In that exemplary embodiment of the invention illustrated in FIGS. 5 and 6, decay pattern modifier 72 is mounted in the preferred location; i.e., on the inner side 63b

of limb 28. This is not required, however; and the decay pattern modifier could instead, if desired, be mounted on the outer side 64b of the limb.

Referring still to the drawings, FIG. 7 depicts, in fragmentary form, a compound bow 88 of the split limb type. The illustrated limb 90 of this bow has two separate, parallel branches 92 and 94 which extend from the end 95 of limb 90 to a location just short of the riser 96 of the bow.

Like the bow 20 depicted in FIG. 1, bow 88 also includes a bow string 98 strung over cams at the ends of the bow's two limbs. One of these cams is shown in FIG. 7 and identified by reference character 100.

A decay pattern modifier specifically designed for a bow of the type just described is depicted in FIG. 8 and identified by reference character 104. This decay pattern modifier may be of the type discussed above and identified by reference character 24 in FIGS. 2 and 3. The stem 106 of decay pattern modifier 104 is fixed to a flat, elongated, generally rigid mount 108. The surface 109 of mount 108 opposite the decay

pattern modifier is coated with a layer 110 of adhesive, the adhesive being covered by a peel away strip 112.

Decay pattern modifier 104 is mounted to the limb 90 of bow 88 (in this case on the outer side 114 of the limb for purposes of clarity only) by removing protective strip 112 from mounting plate 108 and then pressing the mounting plate onto limb 90 of the bow to fix it in place. The mounting plate 108 is oriented: (1) with its longitudinal axis 116 at right angles to the longitudinal axis 118 of limb 90, (2) with the mounting plate spanning the gap 120 between the two branches 92 and 94 of limb 90, and (3) with the mounting plate 108 centered on gap 120 to provide equal area contact between the plate and the branches 92 and 94 of the bow limb.

An alternate arrangement for attaching a decay pattern modifier as disclosed herein to the limb of a split limb bow is illustrated in FIG. 9. The decay pattern modifier is shown in more detail and identified by reference character 124 in FIG. 10. The bow shown in FIG. 9 may duplicate the bow illustrated in FIG. 7. Therefore, the

bow and its illustrated components have been identified by the same reference characters in both FIG. 7 and FIG. 9.

Decay pattern modifier 124 has an integral head 125 and stem 126 providing the same mushroom shape as the decay pattern modifier discussed above and the same patterns of movement as is suggested by ellipse 47 and arcs 54 and 56 in FIG. 3.

NAVCOM is the preferred material from which stabilizer-associated decay pattern modifier 124 is fabricated. The dimensions of decay pattern modifier 124 may essentially duplicate those of the previously described decay pattern modifiers:

Decay pattern modifier 124 promotes accuracy in much the same manner as limb-associated decay pattern modifiers 22 and 24. Specifically, when bow string 98 is released, vibrations which have an adverse effect on accuracy are unavoidably set in the bow and are transmitted from the stabilizer through the bow to the archer's hand despite stabilizer 140. Decay pattern modifier 124 alters the decay pattern of these vibrations in a manner which markedly reduces, if it does not entirely eliminate, the accuracy-reducing effect of those vibrations.



Referring now specifically to FIGS. 10 and 11, the stem 126 of decay pattern modifier 124 is fixed to a flat, circular, generally rigid mount 128, which has a centrally located, internally threaded aperture 130.

Employed with decay pattern modifier 124 are: (1) a flat, also rigid washer 132 with a central aperture 134, and (2) a machine screw 136. Decay pattern modifier 124 is mounted to the limb 90 of bow 88 by placing the decay pattern modifier on one side of limb 90 (again, the outer side 114 of the limb has been chosen, only for purposes of clarity).

Next, washer 132 is aligned with mount 128 on the opposite side of limb 90. Then, machine screw 136 is displaced through the aperture 134 in washer 132 and the gap 120 between split limb prongs 92 and 94 and threaded into mounting component aperture 130. This clamps split limb prongs 92 and 94 between the mounting component 128 and washer 132, securing decay pattern modifier 124 in place.

In those embodiments of the invention depicted in FIGS. 4, 7, and 9, the decay pattern modifier is also preferably located toward the outer end of the limb to

which it is mounted for maximum effectiveness. Decay pattern modifiers mounted on the inside of a bow's limb (see FIGS. 1 and 9 as examples) are mounted far enough down the limbs of the bow from the outer ends of the limbs to which they are mounted that the modifiers will not be struck by the inner run 139 of bowstring 32 when an arrow is released. This insures that the rebounding run 139 of bowstring 32 in will not knock the decay pattern modifier off the bow when the arrow is released. Typically a 0.75 in. distance between the inner run at rest and the head of the decay pattern modifier is sufficient

Turning now to FIGS. 12 - 14, compound bows are commonly equipped with a hydraulic stabilizer intended to offset the degradation in accuracy attributable to the vibrations set up in the bow when an arrow is released.

A stabilizer of the type in question will typically take the form of an elongated cylinder. A stabilizer of that type is depicted in FIG. 12 and identified by reference character 140. The stabilizer is mounted to, and extends forwardly from, the riser 30 of bow 20.

A significant increase in stability, attributable to a modification of vibration decay pattern, can be gained by assembling a decay pattern modifier of the type disclosed herein to the forward end 142 of stabilizer 140. A decay pattern modifier of the type depicted in FIGS. 2 and 3 can be employed or, alternatively, one may for example use a double headed decay pattern modifier of the type shown in detail in FIGS. 12 and 13 and identified by reference character 144. Decay pattern modifier 144 has two integral, disc-shaped heads 146 and 148 separated by an integral stem 150. A second, also integral stem 152 protrudes from the second head 148, and a threaded fitting (or decay pattern modifier mount) 154 is attached to the free end 156 of stem 152.

Decay pattern modifier 144 is fabricated from the same types of material as decay pattern modifier 24, and the decay pattern modifier is dimensioned so that stems 150 and 152 can oscillate in a  $360^\circ$  arc about the longitudinal axis 158 of decay pattern modifier 144 with the peripheral edges and of the two heads 146 and 148 of the decay pattern modifier being free to oscillate in  $360^\circ$  arcs generally parallel to axis 158 as indicated by the double headed arrows 160 and 162 in FIG. 13, and the decay pattern

modifier otherwise being able to wiggle and jiggle in a manner effecting the beneficial decay pattern modification.

Decay pattern modifier 144 is assembled to the outer end 142 of stabilizer 140 by threading the stem 164 of damper mount 154 into a drilled and tapped, blind aperture 165 in the outer end of stabilizer 140-- i.e., that end opposite the riser 30 of the bow.

FIGS. 15 and 16 show a variant 166 of the stabilizer-associated decay pattern modifier just described. The stem 168 of decay pattern modifier 166 is attached as by adhesive 170 to one end of a mount 172. This mount is formed from a polymer with sufficient rigidity that a blind aperture 174 can be drilled and tapped in the opposite end of the mount. A fastener threaded into aperture 174 and into a like aperture 176 in the end 178 of stabilizer 180 mounts decay pattern modifier 166 to the stabilizer.

As shown in FIG. 15, a second threader fastener 182 with two segments 184 and 186 may be supplied with vibration pattern modifier 166 in addition to, or in lieu

of fastener 175. This makes the vibration pattern modifier usable with stabilizers having different diameters of accessory accepting recesses.

Shown in FIG. 19 is the limb 180 of a split limb compound bow which may duplicate the bow 20 illustrated in FIG. 1. The bow is, in this case, equipped with yet another type of decay pattern modifier embodying the principles of the present invention.

One of the two essentially identical vibration pattern modifiers with which the bow is equipped is identified in FIG. 19 by reference character 192.

Vibration pattern modifier 192, shown in more detail in FIGS. 20 and 21, has a head 194, an integral stem 196, and essentially the same overall dimensions as damper 22. Like the latter, vibration pattern modifier 192 is preferably, though not necessarily, fabricated from NAVCOM. Vibration pattern modifier 192 differs from its FIG. 2 counterpart primarily in that material is eliminated from head 194 and, to a considerable extent, from stem 196, leaving recesses 198 and 199 surrounded by walls 200 and 201 in the head and stem of the vibration pattern modifier.

Vibration pattern modifiers with a solid cross section – for example, those shown in FIGS. 2, 6, 8, and 10-- have in some cases been found to be so effective in damping vibrations set up in a bow when an arrow is released as to overstress the bow limb, causing it to fail. Also, in some cases, the vibrations are damped so effectively that the vibration pattern modifier fails. The manner in which the vibrations are damped can be so modified as to avoid the just-discussed problems by "hollowing out" the decay pattern modifier as shown in FIGS. 20 and 21.

Vibration pattern modifier 192 is fastened to the bow limb 190 as by the illustrated adhesive 202 or in any other convenient manner.

It will be apparent to the reader that the invention may be embodied in many forms in addition to those disclosed herein without departing from the spirit or essential characteristics of the invention. The present embodiment is therefore to be considered in all respects as illustrative and not restrictive. The scope of the invention is indicated by the appended claims rather than by the foregoing description and the



## CLAIMS

What is claimed is:

1. In combination:

a bow which comprises a riser and limbs extending in opposite directions

from opposite ends of said riser; and

a component operatively associated with each of said limbs for modifying

the decay pattern of the vibrations set up in the limbs of said bow when an arrow is

released.

2. A combination as defined in claim 1 in which the bow has solid

limbs.

3. A combination as defined in claim 1 in which the bow has split

limbs.

4. A combination as defined in claim 1 wherein the components

associated with the limbs of the bow are alike.



5. A combination as defined in claim 1 wherein each decay pattern

modifying component:

has a head and a stem integrated with said head; and

is fabricated from an elastomeric material.

6. A combination as defined in claim 5 wherein:

the stem of each decay pattern modifying component is fixed at an exposed end to that limb of the bow with which it is associated; and

the decay pattern modifying component is so capable of wiggling and jiggling as to effect said modification of vibration—decay pattern.

7. A combination as defined in claim 5 wherein each of the decay

pattern modifying components comprises an adhesive on an exposed end of the

component's stem for attaching the component to the associated bow limb.

8. A combination as defined in claim 5 wherein:

a rigid element is so fixed to an exposed end of the stem of each decay

pattern modifying component to strengthen the union of said component to the associated

bow limb.

9. A combination as defined in claim 8 in which each of the decay

pattern modifying components has an adhesive on an exposed face of the rigid element.

10. A combination as defined in claim 5 wherein:

each decay pattern modifying component comprises an integral, threaded

fastener; and

there is a complementary threaded insert in the associated bow limb and

extending through a gap between branches of said limb into which the fastener is

threaded.

11. A combination as defined in claim 10 which comprises:

a first element fixing said one component to said bow limb segment; and

a second element for fixing the decay pattern modifier to said second

component.

12. A combination as defined in claim 5 in which:

each limb of the bow has a split limb segment comprising two parallel

branches with a gap therebetween; and

each decay pattern modifier comprises components for clamping the

modifier to the split segment of the associated limb.

13. A combination as defined in claim 12 wherein the components for

securing the modifier to the split limb segment of the associated bow limb comprise:

a first component which is fixed to an exposed end of the vibration decay pattern modifier stem and is seated on one side of the split limb segment;

a second, complementary component seated on the opposite side of the split limb segment; and

a fastener arrangement for clamping the first and second branches of the split limb segment between said first and second components.

14. A combination as defined in claim 13 wherein said fastener

arrangement comprises:

an internally threaded component integrated with said first component; and

a complementary, externally threaded element integrated with said second component and threadingly engageable with the first internally threaded component.

15. A combination as defined in claim 2 in which the elastomeric material from which the decay pattern modifying components are fabricated comprises a visco-elastic mixture of chloroprene and butyl polymers.

16. A combination as defined in claim 2:

which includes a bow string; and

wherein each of the bow limbs has an inner side facing the bow string and an outer side.

17. A combination as defined in claim 16 wherein each decay pattern modifying component is mounted to the outer side of the associated bow limb.

18. A combination as defined in claim 16 wherein;

each decay pattern modifying component is mounted to the inner side of the bow limb with which it is associated; and

the component is so located along the associated bow limb as to space the head of the component sufficiently far from the bow string that said bow string does not interfere with the decay pattern modifying wiggling and jiggling of the component or knock the component off the bow limb when an arrow is released.

19. A combination as defined in claim 5:

which comprises a fastener for mounting each of the decay pattern modifying components to its associated bow limb, each said fastener having:

a head embedded in the stem of the associated decay pattern modifying component; and

a shaft having an externally threaded segment protruding from said stem.

~~20.~~ In combination:

an archery bow;

a bow stabilizer; and

a device for modifying the decay pattern of vibrations set up in said bow

and said stabilizer when an arrow is released;

said bow comprising a riser and limbs at opposite ends of said riser;

said stabilizer comprising an elongated member having first and second

ends, the first end of the elongated member being fixed to the riser of the bow; and

the decay pattern modifying member being fixed to the second end of said

member.

21. A combination as defined in claim 20 wherein:

the decay pattern modifying device has a stem and a head integral with

said stem and is fabricated from an elastomeric material;

it is an end of said stem that is fixed to the stabilizer; and

the device is free to wiggle and jiggle when an arrow is released and

vibrations are consequentially set up in the stabilizer away from the longitudinal axis of

the component.

22. A combination as defined in claim 21 wherein:

the stem of the decay pattern modifying device has a first segment which is fabricated from said elastomeric material and is juxtaposed to the head of the component; and

said device has a second segment which is fabricated from a more rigid material and is fixed to the first segment of the stem.

23. A combination as defined in claim 22 which comprises a fastener for attaching the decay pattern modifying device to the stabilizer member.

24. A combination as defined in claim 23 in which the fastener is threaded into the second segment of the decay pattern modifying device and has an exposed, externally threaded portion which can be threaded into a complementary, internally threaded recess in the second end of the bow stabilizer.

25. A combination as defined in claim 21 wherein there is an adhesive bond between the stem of the decay pattern modifying device and the second end of the stabilizer member.

26.

A device for modifying the decay pattern of the vibrations set up in an archery bow when an arrow is released, said device comprising:

a vibration pattern modifying component which has an integral head and stem and is fabricated from an elastomeric material; and

a mechanism for attaching said component to a bow limb.

27. A device as defined in claim 26 in which the head and stem of the device are so configured and related that:

the head and stem of the device are free to wiggle and jiggle when an arrow is released and vibrations are consequently set up in the bow.

28. A device as defined in claim 26 in which the elastomeric material from which the decay pattern modifying components are fabricated comprises a mixture of chloroprene and butyl polymers.

29. A device as defined in claim 26 in which the component attachment mechanism comprises a layer of adhesive.



30. A device as defined in claim 26 in which the component attaching mechanism comprises:

a threaded fastener integrated with said component; and

a complementary, internally threaded insert which is of sufficient rigidity to hold said fastener and is adapted to be installed in the limb of a bow with which the decay pattern modifying device is to be associated.

31. A device as defined in claim 26:

which is designed for a split limb bow; and

has an attachment mechanism comprising a rigid mount which: (a) is fixed to an end of said stem, and (b) is dimensioned and configured to span a gap between branches of a split bow and to be fixed to said branches.

32. A device as defined in claim 31 in which the attachment mechanism comprises an adhesive for securing the mount to the branches of the split bow limb.

33. A device as defined in claim 26 in which the attachment mechanism comprises first and second clamp elements adapted to be seated on opposite sides of a split bow limb having two branches with a gap therebetween;

a threaded fastener so integrated with the first clamp element as to be extendible through a gap between two branches of a split bow limb; and

a fitting integrated with the second clamp element into which the fastener can be threaded;

said vibration pattern modifying component being fixed to the second clamp component.

34. A decay pattern modifier for an archery bow stabilizer, said modifier comprising:

a first component which has an integral head and stem and is fabricated from an elastomeric material;

a second, internally threaded component which is affixed to the first component; and

a fastener which is threadable into the second modifier component;

the second component of the decay pattern modifier being sufficiently rigid

to retain the fastener in said second component of the decay pattern modifier.

35. A decay pattern modifier as defined in claim 34 in which the head

and stem of the first modifier component are so related that the component can wiggle

and jiggle when an arrow is released and thereby modify the decay pattern of vibrations

setup in the component of the bow to which the decay pattern modifier is attached.

move in any and all directions in a 360° arc relative to a longitudinal axis of

the modifier; and

any and all peripheral portions of the head of the first decay pattern

modifier component can oscillate toward and away from the stem of said first component.

36. A decay pattern modifier as defined in claim 34 in which the

material from which said first component is fabricated comprises a mixture of

chloroprene and butyl polymers.

37. A decay pattern modifier as defined in claim 34 which has an integral, annular element spaced along said stem from said head; said annular element being free to wiggle and jiggle with said stem and said head.

[illegible]

- 35 -

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 14






FIG. 12




FIG. 13




FIG. 15




FIG. 16




FIG. 17

## TIME ANALYSIS




FIG. 18

## SPECTRAL ANALYSIS




FIG. 19




FIG. 20




FIG. 21

